


## Charakteristika



- Specially designed to be installed on doors of industrial cold stores and freezers with big temperature differences.
- The Twin Kool air curtain system has been designed to offer a versatile solution for any type of cold room. It has two jets of opposing air chambers that create additional space between the chamber and the pre-chamber. Thanks to the double barrier, this model becomes the perfect alternative to the TRIOJET SYSTEM air curtain when space is limited or this model is not an option.
- Konstrukcija samoodrživog kućišta napravljena od galvanizovane čelične ploče, završeno u strukturalnoj epoksi-poliester slikarskoj beloj boji RAL9016 kao standardnoj. Druge boje ili nerđajuči čelik su dostupne na zahtev.
- Velika brušena ulazna rešetka koja ne zahteva intenzivno održavanje.
- Anodizirani aluminijumski ispusni kraci, aerodinamičnog oblika., prilagodjivi od 0 do 15 stepeni svake strane.
- Centrifugalni ventilatori sa duplim otvorom pokretani spoljašnjim motorom rotora, sa niskim nivoom buke. Selektor 5 brzina. EC modeli sastavljeni sa veoma štedljivim i efikasnim ventilatorima.
- "A" tip bez grejanja, samo vazduh.
- Advanced Plug&Play control. Includes: Advanced PRO control with LCD display and integrated thermostat, door contact, 7m and remote control. With integrated functions: door delay (configurable); interface mode; operation, alarm and maintenance warning signals; and multiple digital inputs that modify the air curtain's operation.
- Includes protective varnish for the electronic board and control.
- Optional:
  - Auxiliary temperature sensors that improve air curtain control and increase energy savings.
  - Clever PRO intelligent control (automatic, programmable, ModBus via PLC, timer, etc.) with an additional temperature sensor.
- Includes varnishing on the PCB to protect it from corrosion.

## Specifikacija

50Hz

| Modelis          | (m <sup>3</sup> /h) | (m) |
|------------------|---------------------|-----|
| TWIN KECG 3000 A | 9,8-13,8            |     |
| TWIN KM 1500 A   | 9,8-13,1            |     |
| TWIN KM 2000 A   | 9,8-13,1            |     |
| TWIN KM 2500 A   | 9,8-13,1            |     |
| TWIN KM 3000 A   | 9,8-13,1            |     |
| TWIN KECM 1500 A | 9,8-13,8            |     |
| TWIN KECM 2000 A | 9,8-13,8            |     |
| TWIN KECM 2500 A | 9,8-13,8            |     |
| TWIN KECM 3000 A | 9,8-13,8            |     |
| TWIN KG 1500 A   | 9,8-13,1            |     |
| TWIN KG 2000 A   | 9,8-13,1            |     |
| TWIN KG 2500 A   | 9,8-13,1            |     |
| TWIN KG 3000 A   | 9,8-13,1            |     |
| TWIN KECG 1500 A | 9,8-13,8            |     |
| TWIN KECG 2000 A | 9,8-13,8            |     |
| TWIN KECG 2500 A | 9,8-13,8            |     |

60Hz

| Modelis          | (m <sup>3</sup> /h) | (m) |
|------------------|---------------------|-----|
| TWIN KECM 1500 A | 9,8-13,8            |     |
| TWIN KECM 2000 A | 9,8-13,8            |     |
| TWIN KECM 2500 A | 9,8-13,8            |     |
| TWIN KECM 3000 A | 9,8-13,8            |     |



Matmenys

